### 產品比較 Product Comparison

# **灣晓穹潭**像 Odorless Paint ≠ Air purification Paint

	ECO-PLUS 環保潔	環保乳膠漆 Environmental friendly emulsion paint	一般乳膠漆 Typical emulsion paint
去 臭 Odor removal	<b>√</b>	X	X
VOC 過濾分解 Absorb and decompose VOC	<b>√</b>	X	X
甲醛過濾分解 Absorb and decompose formaldehyde	<b>√</b>	X	X
控 濕 Humidity regulation	<b>√</b>	X	X
防止結露 Dew prevention	<b>√</b>	X	X
VOC 含 量 VOC Content	<0.5g/L	較 低 Low	較高 High
油漆氣味 Odor of the paint	不易察覺 Not noticeable	不易察覺 Not noticeable	有 Yes
多款紋理選擇 Variety of texture	<b>√</b>	X	X

Product of Japan, manufactured by **Fujiwara Chemical Co., Ltd.**94 Oshinden, Saijo City, Ehime 799-1342, Japan.

Distributed by

CAP Global Limited 川林有限公司

www.cap-global.com.hk

電話: 35681719



90534401



## **Fujiwara**

# ECO 環保潔珪藻土內牆漆 PLUS

會 呼 吸 的 內 牆 漆 The paint that breathes



#### 產品特點

#### **Product Features**



調濕性 **Humidity Regulation** 

當室內濕度上升時,會吸收空氣中濕氣,當空氣 乾燥 時釋放 出來,避免突然的濕度變動。

Regulate humidity by absorbing moisture when humidity is high and releasing moisture when humidity is low,



空氣淨化 Air Purification

有效過濾室內空氣中之有害氣體,例如惡臭、 VOC和甲醛等。

Effectively absorbing harmful gases like bad smell, VOC, formaldehyde in the air.



不含 VOC Non VOC

VOC 含量接近零\*。

VOC content near zero\*.

- \*天然物料亦含微量 VOC。
- \*Natural raw material also contains minimal VOC.



**Fire Resistant** 



吸著分解 Absorb and decompose

甲醛等有害氣體先被吸著後再被光觸媒分解為無 害物質,不會重新釋放回空氣中。

Harmful gases like Formaldehyde are absorbed by diatomaceous earth and then decomposed by photocatalyst, They will not release again into the air.



防止結露 **Dew Prevention** 

防止結露 (倒汗水) 在牆壁和玻璃窗表面形成, 防霉效果優越

Prevent dew formation on wall and window. Help to avoid mold growth.



Thermal insulation

中於珪藻十導熱系數低,保溫隔熱功效好。冬暖

Low thermal conductivity and good heat insulation.



款式多樣 Variety of texture

#### 產品資料 Product Information

#### 珪藻土 Diatomaceous earth

珪藻土是水中的珪藻植物在死後堆積形成的一種 化石性積土。玤藻土是天然材料,不含有害化學 物質,其微細孔比木炭還要多出 5000 到 6000 倍,除了具有不燃、隔音、防水、比重輕以及很 強的隔熱性之外,還具有除濕、除臭、淨化室內 空氣等多種作用,是十分優良的環保型室內裝修 材料。



珪 藻 Diatom

Diatomaceous earth is the deposit of the fossilized shells of diatoms, which are one-celled plants in waters. Its surface has micro-pores 5000 to 6000 times more than char coal. Beside non-combustible, sound insulating, waterproofing and thermal insulating, it also has the properties of moisture adsorption, odor removal and air purification.



玤 藻 ± Diatomaceous earth

#### 藤原環保潔F系 Eco-Plus F Series

Packing 理論施工度 Coverage

包 裝

漆油系統

System

18公斤 18kg

約5平方米/公斤/層 Around 5m<sup>2</sup> / kg / coat

#### 兩層

- \*如底層粉化,應先塗上底漆。 Two coats
- \* If the substrate is dusty, coated with primer finish.

可使用油轆或噴槍。 Applied with paint roller or spray gun.

